



RP-i25N

Reversible compactor plate

PRODUCT-INFORMATION

Technical Data

RP-i25N

Engine / Drive	1-cylinder-4-stroke-OHV LONCIN G200F petrol engine	
Engine power	kW	4,1 at 3.000 rpm
Displacement	cm ³	196
Gasoline tank volume	Liter	3,6 / ROZ 91 or higher
Engine oil tank	Liter	0,6 / SAE 10W-30/40
Base plate length	mm	630
Base plate width	mm	400
Frequency	Hz	67
Force	kN	25,0
Surface performance	m ² /h	500
Max. Feeding rate	m/min	25
Vibrating impacts	VPM	4300
Compaction depth	cm	30
Max. permissible inclination of the motor		20°
Sound power level	L _{WA}	108 dB(A)
Deadweight	kg	ca. 131
Shipping weight (net / gross)	kg	ca. 135/140
Packaging dimensions (L/W/H)	mm	710 / 430 / 1100

Clear rubber mat,
wheel set and water
tank included



Art. No.: RPi25N

EAN: 40 47424 00706 8



Water tank



water sprinkler

Equipment Features:

- The RP-i25N vibratory plate with forward and reverse motion is the ideal tool for subsoil consolidation and for compacting small to medium-sized areas. It can be used especially in gardening and landscaping, for the construction of walkways and terraces, for laying pavers, in foundation construction, in trench and channel construction, and also for compacting interlocking pavers.
- Water sprinkling is indispensable when compacting very dusty substrates, as well as for all asphalt and tar work! The water is distributed in front of or under the slab through a nozzle pipe. The water quantity is adjustable and the tank is removable.
- It is much more handy and maneuverable than a vibratory plate that only moves forward.
- Stepless regulation of the movement in both directions.
- Equipped with V-belt protected on all sides, compact protective frame, wheel set and polyurethane plate.

Accessoires:

Spare rubber mat clear, 3-pcs. (Art. No. 5G3RP130HPC, EAN: 40 47424 00594 1)

Spare wheel set (Art.No. 5FRP130HPC, EAN: 40 47424 00595 8)